

SINWAN AC Skeleton Fan

AC Skeleton Fan Nomenclature

SK 109 AP - 22 - 1 (W B FG)

Series Name
SK-Plastic Impeller

Frame Size(mm)

- 825 : Dia.75x24
- 80 : Dia.75x37
- 92 : Dia.85x24
- 938 : Dia.85x37
- 125 : Dia.113x24.5
- 109 : Dia.113x37
- 127 : Dia.116x37.5
- 162 : Dia.143x50
- 172 : Dia.140x56
- 180 : Dia.160x63

Frame
AP-Aluminum die casting
Black color
AN-Aluminum die casting
Natural Treatment

Voltage,VAC
11-(110V~115V)
22-(200V~240V)
38-(380V~420V)
44-(440V~480V)
2-(12V)
4-(24V~28V)
8-(42V~48V)
dual voltage
11/22(100V~115V/200V~240V)

Connecting
W-Wire lead
Type

Speed
1-High Speed
2-Medium Speed
3-Low Speed
3(33)-Extra Low Speed
1/2-Dual Speed (High/Medium)
1/2/3-Multiple (High/Medium/Low)

Optional function
F-F/G Tachometer
R-R/D Alarm for motor
slow down

Bearings
B-Two Ball bearings

MK 180 AP 22 - 1 (W B FG)

Series Name
MK-Metal Impeller

Frame Size(mm)

- MK280 : Dia.245x87
- MK254 : Dia.219x87
- MK205 : Dia.197x79
- MK200 : Dia.172x79
- MK180 : Dia.160x80
- MK176 : Dia.160x63
- MK172 : Dia.140x56
- MK150 : Dia.140x44
- MK109 : Dia.113x35
- MK1232 : Dia.113x29
- MK938 : Dia.85x35
- MK838 : Dia.75x35

Frame
AP-Aluminum die casting
Black color
AN-Aluminum die casting
Natural Treatment

Voltage,VAC
11-(110V~115V)
22-(200V~240V)
38-(380V~420V)
44-(440V~480V)
2-(12V)
4-(24V~28V)
8-(42V~48V)
dual voltage
11/22(100V~115V/200V~240V)

Connecting
W-Wire lead
Type

Speed
1-High Speed
2-Medium Speed
3-Low Speed
3(33)-Extra Low Speed
1/2-Dual Speed (High/Medium)
1/2/3-Multiple (High/Medium/Low)

Optional function
F-F/G Tachometer
R-R/D Alarm for motor
slow down

Bearings
B-Two Ball bearings

